

Surface Wave Probe




Ordering Information:

AS2.5-66L

Series Code ————
 Frequency ————
 Connector Type ————
 Crystal dimension 6×6

Application:

Mainly used for surface defect testing and also for surface crack depth testing.



Series Code	Crystal Size (mm)	L	W	H
AS	6×6	24.5	12.5	18
	10×10	28.5	14.8	24

Series Code	Frequency (MHz)	Crystal Size (mm)	Connector Type
AS	2.5/5	6×6, 10×10	L: LEMO 00/ MD: Microdot

Spot-Weld Probe




Ordering Information:

SW15-3L

Series Code ————
 Frequency ————
 Connector Type ————
 Crystal dimension $\Phi 3$

Application:

Straight-beam probe with soft protective membrane, using water column as water delay coupling, so as to achieve optimal coupling between the probe and spot weld surface. Especially good for spot-weld testing on thin plates of automotive industry.



Series Code	Crystal Size (mm)	D	H
SW	$\Phi 3/\Phi 4/\Phi 5/\Phi 6/\Phi 7/\Phi 8$	$\Phi 16$	33

Series Code	Frequency (MHz)	Crystal Size(mm)	Connector Type
SW	15	$\Phi 3, \Phi 4, \Phi 5, \Phi 6, \Phi 7, \Phi 8$	L: LEMO 00/MD: Microdot